

HOGTUNES

Audio Solutions For The Great American Cruiser

Hogtunes Inc. Unit#14-70 Ellis Drive, Barrie, Ontario, Canada, L4N-8Z3

Tel: (705)-719-6361 Email: info@hogtunes.com

RR PLUG-AA Manual

**For Use On 2006-2013 “Non-CVO” Street Glide,
Electra Glide Classic and Road Glide With
Factory Radios Installed**

Standing in front of the bike with the faring off and looking at the back of the radio, the 35 pin plug will plug into the empty “socket” on the right side of the radio, noting it can only go in one way. Please make sure it is all the way in and that the locking tab “clicks” to ensure proper connection.

For applications where radio power will be used, the black 4 pin plug on the end of the RR PLUG-AA will plug directly into the supplied wires harnesses that come with Hogtunes Rear Speaker Pods and Hogtunes saddlebag speaker lid kits. The black plug can also plug directly into the rear input plug on Hogtunes NCA 450-AA Amplifiers. Please see note below.

For use with non Hogtunes amplifiers the 4-pin plug can be cut off and wired in to the amplifier directly. If you do this, please take your time and make sure you have good connections!

NOTE: This plug accesses the rear speaker leads of the radio but DOES NOT activate your radios fader control. To have your fader function “turned on” you must go to a Harley-Davidson® dealer and have the radio “re-flashed”.