

HOGTUNES

Audio Solutions For The Great American Cruiser

Hogtunes Inc., Unit 14 - 70 Ellis Drive, Barrie, Ontario, Canada, L4N-8Z3

Tel: (705) - 719-6361 Email: info@hogtunes.com

www.hogtunes.com

2 Channel Side Plate (2CHSP) Installation Instructions **For Use On 1998-2013 FLH "Batwing" Model Bikes**



On the brake side of the bike, remove the 3 factory bolts shown by arrows (above), noting the brake side fairing support bracket will be removed, and not re-used. Install the plate into the bike using the factory fasteners just removed noting its best to loosely install all 3 fasteners before tightening. Using the supplied "hook and loop" material, secure the amplifier to the plate so it is oriented with the power harness at the bottom. If you are installing a Hogtunes model REV 225-AA, the extra length of that amp will sit below the main plate by approx 1/2" and to the left (brake side) by approx 1/2" so the outer fairing will go back on. You need to adjust accordingly.

This kit includes a wire harness with white/black and red/black wires. If you have a Hogtunes 4 Channel amp, and are adding a Hogtunes 2 channel amp, the supplied harness will plug into the "bypass out" on the 4 channel amp. This is what sends music from the 4 channel amp to the 2 channel amp. The white/black pair of wires on the supplied harness will plug into the yellow/black wires (clutch side input) on the 2 channel amp. The red/black wires on the supplied harness will plug into green/black (brake side input) on the 2 channel amp. Hogtunes lids and lower fairing speaker kits come with the harnesses to get music from the amp to them. For other installs, you can modify the output harness that came with your amp noting blue is brake side, and brown is clutch side.

If you have any questions, please email tech@hogtunes.com or call 705-719-6361.

PowerSports
AUDIO INC.